

## **BMW Racing Drivers Club**

### **Class A1 / A2 / A3**



#### **Class A1:**

Maximum **285** bhp per tonne (Slicks & Wets Tyres to be used) NO MINIMUM WEIGHT

#### **Class A2:**

Maximum **245** bhp per tonne (Slicks & Wets Tyres to be used) NO MINIMUM WEIGHT

#### **Class A3:**

Maximum **220** bhp per tonne (Slicks & Wets Tyres to be used) NO MINIMUM WEIGHT

### **Aero Kits & Bodykits**

Aero kits and bodykits and windows

- Front undertrays are permitted provided they do not extend further back than the front cross member
- Front splitter extend forward 100mm. refer to the blue book
- No rear diffusers
- All bodykits allowed to a maximum width of 1900mm
- Underside bodyshell contours must remain as production, no aero devices are permitted on the underside of the body, except for front under trays
- Rear spoilers are free, refer to the blue book for positioning
- Cars must use standard suspension pickup points.

### **Engine**

Alternative engines or internal engine parts are permitted to be fitted from one model to another. Value Gear, Camshafts and Pistons are Free.

With the provisions that the above is adhered to, engine modifications are unrestricted except as shown in 5.7.2

### **Suspension**

Modification to the suspension is subject to the following conditions:

The spring and damper configuration and all of the original mounting points must be retained and used in the operation of the suspension for that particular model except that coil over dampers may be used on the rear. The replacement of bushes by adjustable spherical bearings is permitted.



## Transmission

Gearboxes may be swapped from model to model. Mounting and Location points must be used as intended by the manufacturer.

## Brakes

All braking components are competitor's choice.

The fitting of Aeroquip brake pipes and removal of the back plates is permitted.

## Wheels & Tyres

18" 17" & 15"

A1	DRY	215/615 R17 S700 - K80	612mm	232mm	220mm	8.0"	7.5" - 9.0"
	WET	215/615 R17 W700 - K22	616mm	232mm	215mm	8.0"	7.5" - 9.0"
A2	DRY	245/645 R18 S700 - K80	643mm	254mm	245mm	9.5"	9.0" - 10.5"
	WET	225/635 R18 W700 - K22	635mm	240mm	234mm	9.0"	8.0" - 9.5"
A3	DRY	225/45 R17 V70A - K91	628mm	224mm	207mm	7.5"	7.0" - 8.5"
	WET	215/615 R17 W700 - K22	616mm	232mm	215mm	8.0"	7.5" - 9.0"
	DRY	245/35 R18 V70A - K91	624mm	251mm	234mm	8.5"	8.0" - 9.5"
	WET	225/635 R18 W700 - K22	635mm	240mm	234mm	9.0"	8.0" - 9.5"



See Championship Regulations for further details



**KUMHO TYRE**

